

BANDKNIFE

TAKAOKA

FEATURES

- Touch panel allows easy adjustments of cutting speed, suitable for cutting different types of materials.
- Digital display of knife speed
- Precise and advanced design minimizes vibration and noise.
- New tension control device helps to maintain proper blade tension.
- Air floating table with ball-shaped nozzles is standard component.
- Trolley wheels for moving the machine.
- Inverter circuit has self-detector which displays error message when the power is overloaded.

STANDARD COMPONENTS

- Inverter motor that allows adjustment of speed
- Ball nozzle air floating table
- Automatic blade sharpener
- Knife cooling silicon pad
- Knife speed digital display



SPECIFICATIONS	TBK-700T	TBK-900T
Cutting Capacity	180mm	180mm
Table size	1500 x 1800mm	1500 x 2100mm
Arm Size	700mm	900mm
Speed Control	570m/min - 1140m/min	570m/min - 1140m/min
Motor	220V 750W	220V 750W
Blower Motor	220V 125W	220V 125W
Dimensions(mm)	1640(L) x 940(W) x 1980(H)	2210(L) x 940(W) x 1820(H)

TAKAOKA CO.,LTD

E-mail : takaoka@takaoka-technocut.co.jp
<http://www.takaoka-technocut.co.jp>

Osaka Head Office 4-6-1, Tatsumi-kita, Ikuno-ku, Osaka, 544-0004, Japan

TEL: +81-6-6751-2500 FAX: +81-6-6751-2510

Network: Nagoya, Okayama, Fukuoka office