

# SPREADER

# TAKAOKA

## TJ-850

For Woven Fabrics

• Suitable for Woven and Denim fabrics.



- Safety Guard  
Two sides (Forward and Backward)  
Safety Guard. (Option)



- Dual material feeding system, which prevents stretching of fabric.
- Specialized for any woven fabric (Roll and Fold).
- Equipped with encoder gear.
- Auto edge alignment and machine stoppage when fabric runs out

- LCD Touch Control Panel  
Easy for operation and adjust settings.  
Available in different languages.




- Feeding Assistant Bar  
Automatic adjustments according to material thickness



- Special Cloth Bar and Roller  
For removing air from nylon fabric.



- Static Eliminator( Option)  
For obviating the charges from nylon



### SPECIFICATIONS

Max Spreading Width	1625mm / 1930mm / 2235mm	Max Spreading Speed	97m/min
Max Diameter of Fabric Roll	700mm	Suitable Materials	Woven Denim etc
Spreading Height	200mm	Spreading Methods	One-Way Spreading · Zigzag Spreading
Max Weight of Fabric Roll	150kg	Power	200V Single Phase 50/60Hz or 220~250V Single Phase 50/60Hz

**TAKAOKA CO.,LTD**

E-mail : [takaoka@takaoka-technocut.co.jp](mailto:takaoka@takaoka-technocut.co.jp)  
<http://www.takaoka-technocut.co.jp>

Osaka Head Office 4-6-1, Tatsumi-kita, Ikuno-ku, Osaka, 544-0004, Japan  
TEL: +81-6-6751-2500 FAX: +81-6-6751-2510

Network : Nagoya, Okayama, Fukuoka office